

701 & 702 Pendant Transmitters



Images are not shown at actual size.

- Reliable, secure Scantronic 868 MHz narrow-band radio operation
- Suitable for use as panic alarms and social alarm triggers
- Two models cater for all applications
- A range of fixings enable the units to be carried or worn on the person
- Water resistant
- Soldered-in lithium battery-powered to ensure operation even if dropped

On your side when you need help most

Hopefully, you'll never need to find out why our pendant transmitters are so highly regarded. But should you ever be attacked, you'll quickly realise why over 750,000 people worldwide trust them with their lives.

Both the 701 & 702 models use our tried and tested 868 MHz narrow-band radio signal for secure, reliable operation. And to ensure your transmitter is always working, the 5 year lithium battery sends a signal when less than one month's operation remains. Moreover, the wide variety of wearing options – including neck pendant, hand-held, brooch and watch strap – means there's a style to suit everyone.

With many other state-of-the-art features (see overleaf), no other range of personal attack transmitters is better equipped to get the help you need when you need it most.

701 & 702 Pendant Transmitters

TECHNICAL SPECIFICATION

Part number	701rEUR-50	701rEUR-60	702rEUR-00
Description	Long range pendant transmitter	Hand-held version of 701rEUR-50	Wristwatch transmitter
Transmit power	10mW	10mW	1mW
Free space range	>700m	>400m	>175m
Power supply (battery)	3v Li non-user replaceable	3v Li non-user replaceable	3v Li non-user replaceable
Battery life	5 years	5 years	5 years
Temperature range	-10 to +55 °C	-10 to +55 °C	-10 to +55 °C
Water resistance	Shower proof	Shower proof	Shower proof to IP65
Dimensions	58 x 40 x 16 mm	58 x 40 x 16 mm	44 x 32 x 13
Weight	34gm	34gm	14gm
Colour	White	White	White
Compliance	EN50131-2 Grade 2, EN61000-6-3:2001, environmental class II	EN50131-2 Grade 2, EN61000-6-3:2001, environmental class II	EN50131-2 Grade 2, EN61000-6-3:2001, environmental class II

COMPATIBLE TRANSMITTERS/RECEIVERS

Scantronic Homelink 75 32 zone radio alarm system
Scantronic 762rEUR-00 2-channel receiver
Scantronic 768rEUR-00 8-32 channel receiver

APPLICATIONS

- Personal panic alarm transmitters
- Social alarm triggers
- Shop worker protection
- Patrolling guard protection
- Nursing staff protection in hospitals and clinics



www.coopersecurity.co.uk

Please contact your local dealer

